JOHN QUAIF
RPII AI113
PIPA 246
Qualified RPII / PIPA
Tester for Inflatables
and Games
JOHNQUAIF@YAHOO.COM
07966 375 571



PAUL QUAIF
RPII Al1112
PIPA 264
Qualified RPII / PIPA
Tester for Inflatables
and Games
PAULQUAIF58@GMAIL.COM
07966 375 570

								3.		
Company Name	S	KY'S	S	THE WIMIT		Addr	ess	12:	3 RIDGE NEVE	remoor
Telephone No	0	77	8	7 563098	5				SWINDO	
Email	INT	90(æ	SMYS-ONTERTAINME			6	JT. CON		
								,		
Serial No P411				77,	Date	Date of Inspection			15.5.202	
Name of Inspector	P	Qu	w	PAUL QUAIF	Expiry Date of Inspe			spection	14.5.200	6
Inflatable Type	(A	n	Size (LxW)			хH	l) (m)	9.2×3.4×2.9	41
Theme	C	SUN	4	EE RUN	M	Manufacturer		rer	AIROUEE	
Place of Inspection				NPON	Date of Manuf			acture	2020	
Structure			-	Anchora	ge	***************************************	7		Blower	
Seams and webbing				Condition of anchor		TV	7	Suitabili	tv	Tu
Bed panels and steps firm		V		Type of anchor point	AND DESCRIPTION OF THE PARTY OF	ANGI	E	_	d outlet mesh	-
Walls and towers firm				Number of anchors		2 1	1	Cable ar	nd plug	
Grounding				Anchor accessories		~	-	Impeller		<u></u>
Sharp angles			1	Structural Ma	aterials			Return F	lap	
Pressure (KPA)	-8			Zips		V		PAT test		L
Entrapment				Ropes	1	1/A		Blower t	ype/electric	
Stability				Windows/netting)	ÝΙΑ		Motor co	over/casing	10
Deflation/Evacuation time	/Evacuation time			Slides				Inhouse tested (PAT)		
Air loss				Slide platform height	t (m)			Blower s	size (Hp)	5
Markings				Height of walls (1st m	1)			Blower t	ube length (m)	.2
Identification				Height of walls (remainder)				Number of blowers (this unit)		
Artwork (no significant peeling)				Platform wall height	(m)			Petrol blowers only		
Bed height (m)	0	6		Run out (m)					a (L x W) (m)	
Open side fall off height (m)	0.	6		Clamber net/foam/la	dder			Numb	er of users and user hei	-
Step and ramp size (m)	N	A		Slide sheet				Maximu	m user height (m)	1.8
Internal wall height (m)	0.	9		Totally Enclosed Structure				Maximum users at 1.0m		
Stitching		1		Exits and markings		1		Maximu	m users at 1.2m	2
Trough depth 7.40				Deflation of user area				Maximu	m users at 1.5m	2
Fabric (fire retardant)				Pressure or user area					m users at 1.8m	2
Fabric (strength)				INSPECTION F				THE RESIDENCE OF THE PARTY OF T	se max user height	+
Thread (non-rotting)				PASS (P)	AIL (F)			height	m users at customised	
Notes / Risk Assessment:	NAI) \	21	7(1) ADN)S 1	1000	Materia (por Oscini Materia Moderna do Prima de			Signature of tester	

This unit must always be used with 2 inch thick, high density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph. This unit must always be supervised by a competent adult who is capable of exercising authority over the users. I certify that the above equipment has been inspected to standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report. If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose. All anchor points must be used to secure the unit to the ground at all times.

Paul Quaif

John Quaif