JOHN QUAIF
RPII AI113
PIPA 246
Qualified RPII / PIPA
Tester for Inflatables
and Games
JOHNQUAIF@YAHOO.COM
07966 375 571

Notes / Risk Assessment:



PAUL QUAIF
RPII AI112
PIPA 264
Qualified RPII / PIPA
Tester for Inflatables
and Games
PAULQUAIF58@GMAIL.COM
07966 375 570

Signature of tester)

Paul Quaif

John Quaif

Address Company Name RIDGE NEVERMOORE **Telephone No** 563098 SWINDON **Email** - ENTERTAINMENT.COM **Serial No Date of Inspection** 15.5.2025 Name of Inspector **Expiry Date of Inspection** WAIF **Inflatable Type** Size $(L \times W \times H)$ (m) Manufacturer Theme AIRQUEE **Date of Manufacture** 2016 Place of Inspection Anchorage **Blower Structure Condition of anchor points** Seams and webbing Suitability Type of anchor point (VC Inlet and outlet mesh Bed panels and steps firm Walls and towers firm Cable and plug **Number of anchors** 10 Impeller **Anchor accessories** Grounding Return Flap **Structural Materials** Sharp angles 31 Pressure (KPA) Zips **PAT test** Ropes Blower type/electric **Entrapment** Windows/netting Stability Motor cover/casing **Deflation/Evacuation time** Slides Inhouse tested (PAT) Slide platform height (m) Blower size (Hp) Air loss Markings Blower tube length (m) Height of walls (1st m) Height of walls (remainder) Identification Number of blowers (this unit) Platform wall height (m) Petrol blowers only Artwork (no significant peeling) Run out (m) Bed height (m) Play area (L x W) (m) Number of users and user height Clamber net/foam/ladder Open side fall off height (m) 8 Slide sheet Maximum user height (m) Step and ramp size (m) Internal wall height (m) **Totally Enclosed Structure** Maximum users at 1.0m N IA **Exits and markings** Stitching Maximum users at 1.2m Deflation of user area Trough depth Maximum users at 1.5m Pressure or user area Fabric (fire retardant) Maximum users at 1.8m Customise max user height Fabric (strength) INSPECTION RESULTS Maximum users at customised FAIL (F) PASS (P) Thread (non-rotting) height

COMMENTS:

This unit must always be used with 2 inch thick, high density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph. This unit must always be supervised by a competent adult who is capable of exercising authority over the users. I certify that the above equipment has been inspected to standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report. If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose. All anchor points must be used to secure the unit to the ground at all times.